

Twin plug and socket connections also to Euro-Standard 220 A, 250V

Under Official Data Sheet L 384, Addendum C

For electrically-operated industrial trucks
Service voltage: 12, 24, 36, 48, 72, 80, 96, 120 and 250 V can be coded

Housing of high-grade plastic

Appliance plug = appliance socket complete, without handle



Length: 86 mm max.
Width: 70 mm max.
Height: 29 mm max.

mm ²	Cat. No.		
	With coding pins for wet batteries	With coding pins for dry batteries	With coding* pins for wet & dry batteries
50	77500	77510	77515
Housing		77540	

*** Plugs or sockets without pilot contacts**
Other connection cross-sections with reducing bushes

mm ²	Cat. No.					
	With coding pins for wet batteries		With coding pins for dry batteries		With coding* pins for wet & dry batteries	
	With 1	With 2	With 1	With 2	With 1	With 2
	* Pilot contact set					
50	77550	77555	77560	77565	77570	77575
* A pilot contact set consists of 1 pilot contact pin and 1 pilot contact bushing						

Plugs or sockets with pilot contacts
Other connection cross-sections with reducing bushes.

In order to equip the twin plug and socket connection with connection cross-sections for 16, 25, or 35 sq. mm leads, reducing bushes must be placed in the contacts. The Catalogue No. for these reducing bushes can be found on the parts list on the following page.

* During assembly, the length of the coding pin will decide whether the plug becomes a socket.
Long coding pin = plug or pin part, short coding pin = socket or tube part.