

Features

- 600 MHz -3dB bandwidth
- 6mA supply current
- Single and dual supply operation, from 5V to 10V
- Fast enable, just 25ns (selected packages only)
- Available in SOT23-5 and SPT23-6 packages
- Dual (EL5292C) and triples (EL5392C) available
- Fixed gain version also available for gains of +1, -1, +2 (EL5196C)
- High speed, 1GHz product available (EL5191C)
- Low power, 4mA, 300MHz product available (EL5193C family, EL5197C family with fixed gain)

Applications

- Video Amplifier
- Cable Drivers
- RGB Amplifier
- Test Equipment
- Instrumentation
- Current to Voltage Converters

Ordering Information

Part No	Package	Tape & Reel	Outline #
EL5192CW5-T7	SOT23-5	7"	MDP0038
EL5192CW5-T13	SOT23-5	13"	MDP0038
EL5192CW6-T7	SOT23-6	7"	MDP0038
EL5192CW6-T13	SOT23-6	13"	MDP0038
EL5192CS	8-Pin SOIC	-	MDP0027
EL5192CS-T7	8-Pin SOIC	7"	MDP0027
EL5192CS-T13	8-Pin SOIC	13"	MDP0027

General Description




The EL5192C is a current feedback amplifier with a very high bandwidth of 600MHz. This makes this amplifier ideal for today's high speed video and monitor applications.

With a supply current of just 6mA and the ability to run from a single supply voltage from 5V to 10V, the EL5192C is also ideal for hand held, portable or battery powered equipment.

The amplifier is also available with a fast acting disable. This disable will turn off in 10ns, and enable again in just 25ns, making the EL5192C amplifier ideal for multiplexing applications. Allowing the \overline{CE} pin to float, or applying a low logic level will enable the amplifier.

For applications where board space is critical, the EL5192C is offered in both the SOT23-5 and SOT23-6 packages, as well as an industry standard 8-pin SOIC. The EL5192C operates over the industrial temperature range of -40°C to +85°C.

Pin Configurations



EL5192C Preliminary

600MHz Current Feedback Amplifier

General Disclaimer

Specifications contained in this data sheet are in effect as of the publication date shown. Elantec, Inc. reserves the right to make changes in the circuitry or specifications contained herein at any time without notice. Elantec, Inc. assumes no responsibility for the use of any circuits described herein and makes no representations that they are free from patent infringement.

élantec

HIGH PERFORMANCE ANALOG INTEGRATED CIRCUITS

Elantec, Inc.

1996 Tarob Court
Milpitas, CA 95035
Telephone: (408) 945-1323
(800) 333-6314
Fax: (408) 945-9305
European Office: 44-71-482-4596

WARNING - Life Support Policy

Elantec, Inc. products are not authorized for and should not be used within Life Support Systems without the specific written consent of Elantec, Inc. Life Support systems are equipment intended to support or sustain life and whose failure to perform when properly used in accordance with instructions provided can be reasonably expected to result in significant personal injury or death. Users contemplating application of Elantec, Inc. Products in Life Support Systems are requested to contact Elantec, Inc. factory headquarters to establish suitable terms & conditions for these applications. Elantec, Inc.'s warranty is limited to replacement of defective components and does not cover injury to persons or property or other consequential damages.

[Amplifiers](#)

Part #	EL5192C
# of Amps	1
Bandwidth @-3 dB (MHz)	600
Min. Gain	1
Supply Voltage Range (Min to Max) (V)	± 2.25 to ± 5.5
Supply Current per Amp (mA)	6
Diff Gain/ Diff Phase (%/f)	0.01/0.01
Input Offset Voltage Max. (mV)	10
Input Voltage Noise nV/Hz	6.5
SlewRate (V/ μ s)	3400
Output Current (mA)	120
Current Mode	✓
Voltage Mode	
Disable	✓
Clamp	
Inputs to GND	
Outputs to GND	
Rail to- Rail in	
Rail to- Rail out	
Package P-DIP	
Package SOIC	8
Package Other	SOT23-5
Data Sheet	PDF FILE