



## MALE DISCONNECTS


### Fully Insulated Nylon Funnel Entry

- Insulation Support





### Nylon Insulated Funnel Entry

- Insulation Grip Sleeve






### Non-Insulated



## PIGGYBACK DISCONNECTS

### Vinyl Insulated

- Insulation Grip Sleeve



Female Tab

Male Tab

PANDUIT® Part Number	Wire Range (mm <sup>2</sup> )	Color Code	Max. Ins.	Dimensions (mm)			Tab Size	Std. Pkg. Qty.	Std. Ctn. Qty.	Bulk Pkg. Qty.	Bulk Ctn. Qty.	Crimp Tools
				A	W	F						
DMNF1-63FIM-C	0.5-1.0	Red	3.45	23.1	10.7	7.9	6.3 x 0.8	100	500	—	—	CT-1525
DMNF2-63FIM-C	1.5-2.5	Blue	4.06	23.1	10.7	7.5	6.3 x 0.8	100	500	—	—	
DMNF1-63M-C	0.5-1.0	Red	3.94	22.9	—	—	6.3 x 0.8	100	500	—	—	CT-1551M
DMNF2-63M-C	1.5-2.5	Blue	4.32	22.9	—	—	6.3 x 0.8	100	500	—	—	
DMNF6-63M-L	4.0-6.0	Yellow	5.84	26.2	—	—	6.3 x 0.8	50	250	—	—	
DM1-63M-C	0.5-1.0	—	—	17.3	—	—	6.3 x 0.8	100	500	—	—	CT-1570
DM2-63M-C	1.5-2.5	—	—	17.3	—	—	6.3 x 0.8	100	500	—	—	
DM6-63M-L	4.0-6.0	—	—	18.3	—	—	6.3 x 0.8	50	250	—	—	
DMV1-63P-C	0.5-1.0	Red	3.68	22.3	7.6	6.3	6.3 x 0.8	100	500	—	—	CT-1551M
DMV2-63P-C	1.5-2.5	Blue	4.06	22.3	7.6	6.3	6.3 x 0.8	100	500	—	—	

Order the number of pieces required in multiples of standard package quantities.  
L = 50 pcs. and C = 100 pcs.