

52-Pin PQFP Package +5 Volt Supply

32 Mb/s Read Channel Electronics

AD899

FEATURES 32 Mb/s Data Transfer Rate Capability Functionally Complete Read Channel Wideband AGC Peak Hold Mode or Averaging 7th Order Bessel Filter Programmable Cutoff Frequency Programmable Equalization Data Qualifier **Amplitude Qualification** Data Polarity Check Data Synchronizer Zero Phase Start-Up **DAC Controlled Center Frequency DAC Controlled Window Center** 1-7 ENDEC Independent Early/Late Precompensation Write Clock Synthesizer 6-Bit M and N Dividers Servo Demodulator A, B, C, D Sampling Slew Rate Limiting or Peak Hold **Power Down Options**

PRODUCT DESCRIPTION

The AD899 offers a functionally complete read channel operating at up to 32 Mb/s and is completely compatible with constant density recording. When it is connected to the output of the head amplifier, it performs the signal conditioning, data qualification, data synchronization and Encoding/Decoding task with a minimum of external components. To support constant density recording, a high performance frequency synthesizer and a programmable titler are also included, as is a servo demodulator to support and bedded servo applications.

The AD899 is ideally suited for a wide variety of applications given its built in peribility. All major read channel characteristics the programmable on the AD899 through a standard serial the serial port controls the following critical characteristics: AGC tetting, filter cutoff frequency and boost, data qualification amount determined the write precompensation amount (Independent Early and Late), M and N divider ratios for the frequency synthesizer, as well as the power down options.

The AD899 will be available in a 52-pin quad flat pack package (PQFP) and is specified to operate over the commercial (0°C to +70°C) temperature range.





Figure 1. Simplified AD899 Block Diagram

This information applies to a product under development, its characteristics and specifications are subject to change without notice. Analog Devices assumes no obligation regarding future manufacture unless otherwise agreed to in writing.

FUNCTIONAL BLOCK DIAGRAM



This information applies to a product under development. Its characteristics and specifications are subject to change without notice. Analog Devices assumes no obligation regarding future manufacture unless otherwise agreed to in writing.