



REVISIONS			
REV	DESCRIPTION	DATE	APPROVED
01 ₁	REVISED	8/16/96	[Signature]

HOUSING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER QQ-P-35
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A
CENTER CONTACT	BERYLLIUM COPPER PER ASTM-B-196 OR ASTM-B-197, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204
CONTACT EXT	IRON-NICKEL-COBALT ALLOY PER MIL-I-23011 CLASS 1 (KOVAR)	GOLD PLATE PER MIL-G-45204
O-RING	FLUROCARBON RUBBER PER MIL-R-83248, TYPE 1, CLASS 1	N/A
HERMETIC SEAL	GLASS BEAD	N/A

COMPONENT	MATERIAL	FINISH
-----------	----------	--------

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRAC. ± 1/64 DEC. ± .005 ANGLES ± 1°	DRAWN BY DC	DATE 7/19/78	AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599
	CHECKED BY RHF	7/24/78	
	APPD BY RHF	7/24/78	

These drawings and specifications are the property of M/A COM Interconnect Div. and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.	USE ASSY PROCEDURE	TITLE "OSSM" HERMETICALLY SEALED JACK - MICROSTRIP TRANSITION -STRAIGHT TERMINAL-		
	NO. A.P. N/A	SIZE B	CODE IDENT NO. 26805	1052-3121-02
		SCALE 6:1		REV 01 ₁

NOTES:
1. CAPTURED CENTER CONTACT

.XXX = in
XX.X = mm (REF)

CUSTOMER DRAWING

AMP PART # 1045594-1
SHEET 1 OF 1 REV A