



SPECIFICATIONS

- Rating: 100mA max, 42 VAC/DC
- Mechanical Life: 1,000,000 cycles
- Contact Resistance: 100 mΩ max.
- Insulation Resistance: 1000 MΩ min.
- Withstanding: 1000 VAC
- Housing: PBT
- Transparent: PC
- Contact: Stainless, Au Plated
- Terminals: Brass, Au Plated
- Terminal Seal: Epoxy

Series	Type	Cap Type	LED Qty	LED Color	LED Brightness
SWT	2KS5	A0	X	X	X
Keylock Switch	15x15mm	A0=Transparent Actuation	0=No Led 1=1 Led 2=2 Leds	1=White 3=Red 5=Yellow 6=Green 7=Blue	None=normal brightness A=Super Bright

RoHS compliant

Rev.	Description	Date	Approved	Drawing	Name	Date
				Approved	Howard	01/19/11
				Checked	Lizzy	01/19/11
				Drawn	Tina	01/19/11
				0.0 ± 0.35	0.00 ± 0.20	Angles ± 3'
				UNIT: mm		

Central Components Manufacturing
 440 Lincoln Blvd., Middlesex, New Jersey 08846
 Phone 732 469-5720 888 288-5152 Fax 732 469-1919

Part No.: **SWT-2KS5-A0-X-0-X-R-A**

Description: Short Travel Keyswitch