HUBER+SUHNER® DATA SHEET
Coaxial PCB Connector: 85_MMCX-50-0-1/111_O

Rev.: E

Description

Right angle PCB jack

Interface Standards
SUHNER-MMCX

Technical Data

Electrical Data

Impedance	50 Ω
Interface frequency max.	6 GHz

Mechanical Data

Board mounting type	through holes
Weight	0.0006 kg

Environmental Data

Operating Temperature	-55 °C to 155 °C
2002/95/EC (RoHS)	compliant

Material Data

Piece Parts	Material	Surface Plating
Centre contact	Copper Beryllium Alloy	Hard Au min. 1.3 µm over Ni min. 1.3 µm
Outer contact	Brass	Hard Au min. 0.8 µm
Body	Brass	Hard Au min. 0.8 µm
Insulator	PFA / PTFE	

Related Documents

Outline drawing	DOU-00083972
Catalogue drawing	DCA-00012837
Mounting hole	DOU-00012639

Ordering Information

Bulk 100 pcs package	85_MMCX-50-0-1/111_OH
Single package	85_MMCX-50-0-1/111_OE
Tape and Reel package	85_MMCX-50-0-1/111_OM

Remarks

PCB connector without stand-offs

HUBER+SUHNER is certified according to ISO 9001 and ISO 14001

WAIVER!
It is exclusively in written agreements that we provide our customers with warrants and representations as to the technical contained specifications and/or the fitness for any particular purpose. The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.

HUBER+SUHNER

HUBER+SUHNER AG
RF Technology
9100 Herisau, Switzerland
Phone +41 (0)71 353 41 11
Fax +41 (0)71 353 45 90
www.hubersuhner.com

HUBER+SUHNER – Excellence in Connectivity Solutions