



ZRSL4-DRL

- 4 Connections

Technical Data


Wire sizes		Insulating Material	
Solid min	0.5 mm ²	Material	PA 6.6
Solid max	6.0 mm ²	Flammability Class	UL 94 V-0
Stranded (flexible) min	0.6mm ²	Temperatures	
Stranded (flexible) max	6.0 mm ²	Working Temperature	-40 - 120 °C
Stranded with Ferrule min	0.5 mm ²	Dimensions	
Stranded with Ferrule max	4.0 mm ²	Width	6.1 mm
		Length	93.0 mm
		Height TS35 x 7.5	42.0 mm

Electrical Data

General


Test Pick off	2
---------------	---

Colours



GREEN/YELLOW

Connection Diagram



Order Data

Article Designation	Article Number	PU
ZRSL4-DRL-GREEN/YELLOW	43527.2	100

Accessoires

Article Designation	Article Number	PU
End Plate ZAP4/4A	493705.2	50
Four-Way Covers ZAD4/4/B	493707.0	20
End Stopn ZES35	493748.2	50
Test Adapter ZTA4	493741.2	10
Quick Labelling PSB6/50	494702.7	500

Ratings

Ratings	CSA	CSAus	IEC
Rated Voltage			
Rated Current			
Rated Wire Size	AWG 20-10	AWG 20-10	4.0 mm ²
Rated Impulse Voltage			8 V
Pollution Degree			3