

Recommended PCB Layout

ELECTRICAL:


CURRENT RATING: 1A
 CONTACT RESISTANCE:
 < 30m Ω Max.
 INSULATOR RESISTANCE:
 > 1000M Ω Min.
 DIELECTRIC WITHSTANDING VOLTAGE:
 750VAC for 1 Minute
 OPERATING TEMPERATURE: -55° C to +85° C

MATERIAL:

INSULATOR: Thermoplastic UL94V-0
 CONTACTS: Gold Plated
 SHELL PLATING: Nickel

MECHANICAL:

CONTACT INSERTION FORCE: 4.0 Kg Max
 CONTACT SEPARATION FORCE: 1.0 Kg Max



HOW TO ORDER:

U 0 0 1 - 0 4 1 X - 8 1 X - Z

NUMBER OF CONTACTS:

04 - 4 PIN SINGLE PORT

DEFINITION:

1 - STRAIGHT

SHELL STYLE

8 - Height 13.7mm Vertical

of LOCKS

1 - 4 Locks

RoHS Compliant

INSULATOR COLOR:

0 - BLACK
 1 - WHITE

SELECTIVE CONTACT PLATING:

1 - Gold
 3 - 15u" Au
 4 - 30u" Au

Rev	Drawn	Checked	Approved	Date
0	B.S.	S.M.	S.M.	2/12/08

SMP TECHNOLOGY, INC.

SCALE: N/A USB CONNECTOR, SINGLE PORT, STRAIGHT, TYPE A (13.7mm Height)